

AQUAGARD 422

DESCRIPTION OF PRODUCT

Aquagard 422 is a clear penetrating liquid which has water repellent and crystalline sealing properties and is used to waterproof a wide variety of masonry surfaces.

GENERAL PRODUCT INFORMATION

Appearance: Clear watery liquid
Packaging: 5 and 25l containers
Storage: Shelf life is 1 year in sealed and unopened containers.
Product should be stored out of direct sunlight with temperature range between 5-35 degrees °C
Specific Gravity: 0,98
PH: 10

AREAS OF USE

- New and old plaster surfaces
- Brickwork
- Concrete
- Slasto
- Sandstone
- Roof tiles

PRODUCT FEATURES AND BENEFITS

- Proven track record of more than 24 years
- Very cost effective
- Permanent waterproofing treatment due to its in depth functionality
- Dual action water repellent and crystalline sealing properties
- Excellent hydrophobic and waterproofing properties
- When applied before painting, it will substantially increase the life of the coating
- The crystalline properties makes the product effective against negative water pressure
- Penetrates surfaces and waterproofs in depth
- Conventional paints adhere well to Aquagard 422 treated surfaces
- Water based. Non polluting and non toxic
- Does not alter the appearance of treated masonry
- Acid and alkali resistant
- Permanent waterproofing solution
- Maintains the appearance of masonry. Prevents unsightly wet patches after rain and prevents fungus growth

LIMITATIONS

Product should be applied to dry surfaces

APPLICATION INSTRUCTIONS

Surfaces should be clean, firm and visibly dry. Aquagard 422 can be applied using a conventional garden sprayer or for bigger jobs a knapsack sprayer. The product should be applied to the point of run off to ensure proper saturation into the substrate. Any excess should be wiped off to prevent crystals forming on the surface. Care should be taken to cover glass and aluminum surfaces during the application. Spillage to be wiped off immediately, as it can be extremely difficult to remove when dry.

COVERAGE

Typical coverage is 4-6 m² per l depending on porosity of surfaces. Only one application is generally required.

DISCLAIMER

Whilst Aquagard makes every effort to ensure that all information given is accurate, the use and application of our products is outside our direct or continuous control, therefore Aquagard cannot accept any direct or indirect liability arising from the use of our products. Aquagard is able to supply a manufacturers guarantee on request. Please contact the Aquagard consultant for further information.

HEALTH AND SAFETY

Please read the product label, technical data sheet and material safety data sheet before use. Do not ingest internally. Avoid contact with eyes. If solution does come into contact with eyes, flush immediately with water and refer to Doctor for medical attention. Avoid prolonged contact with skin or breathing in of mist or fumes. Wear a suitable face mask. Keep out of reach of children. Take due care and precaution when applying the product especially if working at heights.



Tel: 011 794 3307 | info@aquagard.co.za | aquagard.co.za
Erf 115, 2 Boat Turn Road, Laser Park, Roodepoort 2040